

## VERNATUBE™

Vernatube™ is resin-impregnated glass filament tubing wound exclusively with a new fire retardant resin formulated for high temperature applications. Centek uses the fire retardant Vernatube™ to fabricate many of the basic components used to manufacture our wet marine exhaust systems. Our Vernatube™ exceeds values for the class of materials designated as “self-extinguishing” per ASTM



PART#	NOMINAL O.D.	NOMINAL WALL	WEIGHT LBS. PER FT.	STD. LENGTH
	IN/MM	IN/MM		IN/MM
1100525	1.00 / 25	0.104	0.03	60.00 / 1524
1100521	1.50 / 38	0.105	0.40	120.00 / 3048
1100522	1.62 / 41	0.113	0.40	120.00 / 3048
1100523	1.75 / 44	0.112	0.40	120.00 / 3048
1100524	1.88 / 48	0.116	0.50	120.00 / 3048
1100512	2.00 / 51	0.125	0.50	120.00 / 3048
1100510	2.25 / 57	0.127	0.50	120.00 / 3048
1100511	2.38 / 60	0.127	0.60	120.00 / 3048
1100501	2.50 / 64	0.128	0.70	120.00 / 3048
1100513	2.88 / 73	0.130	0.80	120.00 / 3048
1100502	3.00 / 76	0.130	0.90	120.00 / 3048
1100503	3.50 / 89	0.135	1.00	120.00 / 3048
1100504	4.00 / 102	0.138	1.30	120.00 / 3048
1100505	4.50 / 114	0.140	1.50	120.00 / 3048
1100506	5.00 / 127	0.144	1.70	120.00 / 3048
1100507	6.00 / 152	0.148	2.00	120.00 / 3048
1100508	8.00 / 203	0.154	3.00	120.00 / 3048
1100509	10.00 / 254	0.160	3.80	120.00 / 3048
1100515	12.00 / 305	0.160	4.60	120.00 / 3048
1100514	14.00 / 356	0.200	6.50	144.00 / 3658
1100516	16.00 / 406	0.200	8.00	144.00 / 3658
1100529	18.00 / 457	0.200	8.50	144.00 / 3658

## VERNATUBE™ (PRE-CUT)

PART#	NOMINAL O.D.	NOMINAL WALL	WEIGHT LBS. PER FT.	STD. LENGTH
	IN/MM	IN/MM		IN/MM
1200507	1.50 / 38	0.105	0.40	36.00 / 914
1200508	1.50 / 38	0.105	0.40	60.00 / 1524
1200509	1.62 / 41	0.113	0.40	36.00 / 914
1200510	1.62 / 41	0.113	0.40	60.00 / 1524
1200860	1.75 / 44	0.112	0.45	36.00 / 914
1200861	1.75 / 44	0.112	0.45	60.00 / 1524
1200769	1.88 / 48	0.116	0.50	36.00 / 914
1200543	1.88 / 48	0.116	0.50	60.00 / 1524
1200511	2.00 / 51	0.125	0.50	36.00 / 914
1200512	2.00 / 51	0.125	0.50	60.00 / 1524
1200862	2.25 / 57	0.127	0.60	36.00 / 914
1200863	2.25 / 57	0.127	0.60	60.00 / 1524
1200864	2.38 / 60	0.127	0.65	36.00 / 914
1200865	2.38 / 60	0.127	0.65	60.00 / 1524
1200770	2.50 / 64	0.128	0.70	36.00 / 914
1200544	2.50 / 64	0.128	0.70	60.00 / 1524
1200715	3.00 / 76	0.130	0.90	36.00 / 914
1200541	3.00 / 76	0.130	0.90	60.00 / 1524
1200513	3.50 / 89	0.135	1.00	36.00 / 914
1200514	3.50 / 89	0.135	1.00	60.00 / 1524
1200515	4.00 / 102	0.138	1.30	36.00 / 914
1200516	4.00 / 102	0.138	1.30	60.00 / 1524
1200866	4.50 / 114	0.140	1.50	36.00 / 914
1200867	4.50 / 114	0.140	1.50	60.00 / 1524
1200517	5.00 / 127	0.144	1.70	36.00 / 914
1200518	5.00 / 127	0.144	1.70	60.00 / 1524
1200519	6.00 / 152	0.148	2.00	36.00 / 914
1200520	6.00 / 152	0.148	2.00	60.00 / 1524
1200872	8.00 / 203	0.154	3.00	36.00 / 914
1200538	8.00 / 203	0.154	3.00	60.00 / 1524
1200873	10.00 / 254	0.160	3.80	36.00 / 914
1200539	10.00 / 254	0.160	3.80	60.00 / 1524
1200756	12.00 / 305	0.160	4.60	36.00 / 914
1200540	12.00 / 305	0.160	4.60	60.00 / 1524